

DECLARATION OF PERFORMANCE



Tradesmith Ltd
Unit 8 Station Road Industrial Estate
Station Road, Hailsham
East Sussex. BN27 2EY. UK

[2013]

DoP No:002 date 12/03/13

B Rated Pvc-u Casement & Tilt & Turn windows, intended for use in domestic or commercial refurbishment or new building applications.

Annex ZA.1 of BS EN 14351-1:2006+A1:2010

Watertightness: NPD

Dangerous substances: none released under normal indoor use.

Resistance to wind load: NPD

Load-bearing capacity of safety devices: pass, 350N when fitted (1)

Acoustic performance: NPD

Thermal transmittance: $\leq 1.6 \text{ W/m}^2\text{K}$ (2)

A Factory Production Control (FPC) system is established, documented and maintained in accordance with AVCP System 3 as per annex ZA.2 of BS EN 14351-1:2006+A1:2010.

(1) Report No's 2370/7479366/1 dated 12/02/2010 for Safety and Security friction hinges with built in restrictor – BSI, Notified Test Body No. 0135

(2) Thermal transmittance calculation approved by BFRC, Notified Test Body No. 021, Ref report No. 2102,2103,2104,2105,4064 & 4065 dated 08/02/2010

M. Hutchinson

Name (Print)

Signed